





**Hex-Socket Head Cap Screw**  
Code: **IMB**



**DIN ISO 4762**  
Class: **12.9**



d (M)	l <sub>mm</sub>	b	D	k	s
<b>M3</b> x 05	10	8.5	5.5	3	2.5
	15	15			
	20	18			
	25	23			
	30	20			
	30	20			
<b>M4</b> x 07	10	8	7	4	3
	15	14			
	20	18			
	25	23			
	30	20			
	35	20			
	40	20			
	45	20			
	50	20			
	60	20			
	70	20			
	80	20			
90	20				
100	20				
<b>M5</b> x 08	10	8	8.6	5	4
	15	14			
	20	18			
	25	23			
	30	22			
	35	22			
	40	22			
	45	22			
	50	22			
	60	22			
	70	22			
	80	22			
	90	22			
	100	22			
	110	22			
120	22				
130	22				
150	22				

d (M)	l <sub>mm</sub>	b	D	k	s
<b>M6</b> x 1	10	7	10	6	5
	15	13			
	20	17			
	25	22			
	30	27			
	35	24			
	40	24			
	45	24			
	50	24			
	55	24			
	60	24			
	70	24			
	80	24			
	90	24			
	100	24			
	120	24			
	130	24			
150	24				
160	24				
<b>M8</b> x 1.25	10	8	13	8	6
	15	13			
	20	17			
	25	22			
	30	27			
	35	32			
	40	28			
	45	28			
	50	28			
	55	28			
	60	28			
	70	28			
	80	28			
	90	28			
	100	28			
	120	28			
	130	28			
140	28				
150	28				
160	28				
180	28				
200	28				
<b>M10</b> x 1.50	20	16	16	10	8
	25	21			
	30	26			
	35	31			
	40	36			
	45	32			
	50	32			
	55	32			
	60	32			
	70	32			
	80	32			
	90	32			
	100	32			
	110	32			
	120	32			
	130	32			
	150	32			
160	32				
180	32				
200	32				
260	32				
300	32				

d (M)	l <sub>mm</sub>	b	D	k	s
<b>M12</b> x 1.75	20	15	18	12	10
	25	20			
	30	25			
	35	30			
	40	35			
	45	40			
	50	45			
	55	36			
	60	36			
	70	36			
	80	36			
	90	36			
	100	36			
	110	36			
	120	36			
	130	36			
	150	36			
160	36				
180	36				
200	36				
260	36				
300	36				
<b>M14</b> x 2	30	24	21	14	12
	35	29			
	40	34			
	45	39			
	50	44			
	60	44			
	70	44			
	80	44			
	90	44			
	100	44			
	110	44			
	120	44			
	130	44			
	150	44			
	160	44			
	180	44			
	200	44			
240	44				
260	44				
300	44				
<b>M16</b> x 2	30	24	24	16	14
	35	29			
	40	34			
	45	39			
	50	44			
	55	49			
	60	54			
	70	44			
	80	44			
	90	44			
	100	44			
	110	44			
	120	44			
	130	44			
	140	44			
	150	44			
	160	44			
180	44				
200	44				
220	44				
240	44				
260	44				
300	44				

d (M)	l <sub>mm</sub>	b	D	k	s
<b>M18</b> x 2.50	40	34	27	18	14
	50	43			
	60	53			
	70	52			
	80	52			
	100	52			
	120	52			
	140	52			
	160	52			
	180	52			
	200	52			
	220	52			
240	52				
260	52				
300	52				
<b>M20</b> x 2.50	40	34	30	20	17
	50	43			
	60	53			
	70	52			
	80	52			
	90	52			
	100	52			
	120	52			
	140	52			
	160	52			
	180	52			
	200	52			
220	52				
240	52				
260	52				
300	52				
<b>M24</b> x 3	50	50	36	24	19
	60	52			
	70	61			
	80	71			
	90	60			
	100	60			
	120	60			
	140	60			
	150	60			
	160	60			
	180	60			
	200	60			
220	60				
240	60				
260	60				
300	60				

Order: **IMB. d x l**